

CLAIMS

What is claimed is:

1. A freeway routing system for a field programmable gate array (FPGA), the FPGA comprising:

- 5 a plurality of FPGA tiles, each FPGA tile comprising:
- a plurality of functional groups (FGs) arranged in rows and columns;
- a plurality of interface groups (IGs) surrounding said plurality of FGs such that one IG is positioned at each end of each row and column, each of
- 10 the IGs having a first, second and third set of input ports and a first, second and third set of output ports;
- a freeway set of routing conductors configured to transfer signals to the first, second and third input ports of IGs in one FPGA, and configured to transfer signals from said first, second and third output ports of the IGs of all other FPGA
- 15 tiles;
- said freeway set of routing conductors comprising:
- a plurality of vertical conductors that form intersections with a plurality of horizontal conductors; and
- programmable interconnect elements located at said
- 20 intersections in a diagonal orientation on said FPGA tile.

2. The FPGA of Claim 1, wherein said FPGA further comprises:

at least one other FPGA tile configured in the same manner as said first FPGA;

wherein the freeway set of routing conductors of each FPGA tile are connected to any adjacent FPGA tile's freeway set of routing conductors.

3. The FPGA of Claim 2, wherein said FPGA further comprises:

programmable interconnect elements located at said connections between adjacent FPGA tiles.

4. The FPGA of Claim 1, wherein said diagonally oriented programmable interconnects are arranged from the upper left corner of said first FPGA tile to the lower right corner of said first FPGA tile.

5. The FPGA of Claim 1, wherein said diagonally oriented programmable interconnects are arranged from the upper right corner of said first FPGA tile to the lower left corner of said first FPGA tile.

6. The FPGA of Claim 1, wherein said freeway set of routing conductors are further configured to also transfer signals from output ports of at least one IO.

7. The FPGA of Claim 1, wherein said freeway set of routing conductors are further configured to also transfer signals from output ports of at least one RAM.

8. A method of routing the internal components in a FPGA tile comprising:

inputting a function netlist defining a user circuit;

optimizing said user circuit;

placing user cells defining said user circuit into said FPGA internal components;

using a first set of routing conductors to route said user circuit to

5 interconnect said internal components to implement said user circuit; and

engaging a freeway set of routing conductors to meet said user circuit routing requirements;

generating a programming bitstream defining said user circuit; and

programming said FPGA functional unit with said bitstream to

10 implement said user circuit.

9. A method of routing the internal components in a FPGA tile comprising:

inputting a function netlist defining a user circuit;

optimizing said user circuit;

placing user cells defining said user circuit into said FPGA internal

15 components;

using a first set of routing conductors and a freeway set of routing

conductors to route said user circuit to interconnect said internal components to

implement said user circuit;

generating a programming bitstream defining said user circuit; and

programming said FPGA functional unit with said bitstream to implement said user circuit.

10. A method of providing a freeway interconnect structure in a FPGA comprising:

- 5 providing a plurality of FPGA tiles;
- providing a plurality of functional groups (FGs) arranged in rows and columns on each said FPGA tile;
- providing a plurality of interface groups (IGs) surrounding said plurality of FGs such that one IG is positioned at each end of each row and
- 10 column, each of the IGs having a first, second and third set of input ports and a first, second and third set of output ports;
- providing a freeway set of routing conductors configured to transfer signals to said first, second and third input ports of IGs of one FPGA tile, and configured to transfer signals from said first, second and third output ports
- 15 of IGs of all other FPGA tiles;
- said act of providing a freeway set of routing conductors comprising:
- providing a plurality of vertical conductors that form intersections with a plurality of horizontal conductors; and

providing programmable interconnect elements located at
said intersections in a diagonal orientation on said FPGA tile.

11. The method of Claim 10 further comprising:

providing at least one other FPGA tile configured in the same
5 manner as said first FPGA; and
connecting said freeway set of routing conductors of each FPGA
tile to any adjacent FPGA tile's freeway set of routing conductors.

121. The method of Claim 11, further comprising:

providing programmable interconnect elements located at said
10 connections between adjacent FPGA tiles.

13. The method of Claim 10, further comprising configuring said freeway set
of routing conductors to also transfer signals from output ports of at least one
IO.

14. The method of Claim 10, further comprising configuring said freeway set
15 of routing conductors to also transfer signals from output ports of at least one
RAM.

15. An apparatus for routing the internal components in a FPGA tile
comprising:

means for inputting a function netlist defining a user circuit;
20 means for optimizing said user circuit;

means for placing user cells defining said user circuit into said
FPGA internal components;

means for using a first set of routing conductors to route said user
circuit to interconnect said internal components to implement said user circuit;

5 means for determining whether the routing requirements of said
user circuit have been met using said first set of routing conductors;

means for engaging a freeway set of routing conductors to meet
said user circuit routing requirements;

means for generating a programming bitstream defining said user
10 circuit; and

means for programming said FPGA functional unit with said
bitstream to implement said user circuit.

16. An apparatus for routing the internal components in a FPGA tile
comprising:

15 means for inputting a function netlist defining a user circuit;

means for optimizing said user circuit;

means for placing user cells defining said user circuit into said
FPGA internal components;

means for using a first set of routing conductors and a freeway set of routing conductors to route said user circuit to interconnect said internal components to implement said user circuit;

means for generating a programming bitstream defining said user circuit; and

means for programming said FPGA functional unit with said bitstream to implement said user circuit.